

Orient Automotive Industries
(Pvt) Ltd.





Imported EN19C Crankshaft



Heavy Duty Top Link

BULL POWER 565



Forged Heavy Duty Hydraulic Chamber Body



Fuel Efficient Original Delphy Brazilian Pump and Injector



High Lux Crystal Head Lamps




SAE 8620 Gearing & Shafting



Heavy Duty General Brand Tyre and Rims





ENGINE	IMR-DM34T
Engine Power	60 HP (BS)
Compression Ratio	15.5 : 1
Injection	Direct
Number of Cylinder	3
Bore (mm)	91.5
Stroke (mm)	127
Capacity (Ltr)	2.5
Aspiration	Turbo Charged
Starting Aid	Thermostart
Throttle Control	Foot & Hand
Cooling	Water
Air Cleaner Type	Oil Bath
Air Pre Cleaner	Over Bonnet
Fuel Filter	Duel, High Capacity
Exhaust	Vertical
Oil Cooler	Air Cooled Fin Type
CLUTCH	
Туре	Duel Clutch, Dry Disc
Diameter (mm)	305 x 254
Diffrential Lock	Mechanical
TRANSMISSION	
Туре	Manual,Constant Mesh,Sliding Spur Gear
Number of Gears	8 Forward, 2 Reverse
POWER TAKE OFF	
Туре	Live Independent Single Speed
Engine Speed at 540 PTO rpm	1789 rpm
Shaft Diameter	35 mm
Number of Splines	6
HYDRAULICS	
Function	Draft, Position, Response Control, Constant Pumping
Pump Type	Reciprocating
Oil Flow	17L/mim
Lower Links	Cat I & II, Interchangeable

NOTE: Orient Automotive Industries (Pvt.) Limited reserves the right to change specifications without notice. The above mentioned values for power and torque are according to manufacturer's standards.

Orient Automotive Industries (Pvt) Ltd.

HEAD OFFICE

Orient Automotive Industries (PVT) Ltd. First Floor, Block-3, Hockey Club of Pakistan Stadium, Liaquat Barracks, Karachi, Pakistan.

(PLANT

Plot # A1 - A50 Nazar Chowrangi, Hub Industrial Trading Estate (HITE) Hub, District Lasbela, Balochistan, Pakistan.

STEERING	
Type	Manual, Worm, Ball & Nut
REAR AXLE & BRAKES	
Brake Type	Oil Immersed Wet Brakes, Multi Disc
Actuation	Mechanical
Axel Type	Straddle with Epicyclic Hub Reduction Unit
Parking Brake	Hand Lever Operated
No. of Disc	4x2 each side
TYRES	
Front	7-50-16, 6PR
Rear	14.9/13-28, 6PR
WHEEL TRACK	
Front	1245-1855 mm
Rear	1420-2130 mm
ELECTRIC	
Voltage	12 V, Negative Earth
Battery	120Ah
Starter Motor	2.2 KW
Alternator	32 Amp.
INSTRUMENTATIO	N
Gauges	Tachometer, Hourmeter, Fuel
	Level, Battery Condition, & Water
	Temperature
Warning Lights	Elect Charge, Low Engine Oil Level,
	Oil Pressure, Turn Indicators, Head
	Light Main Beam & Auxiliary Socket.
CAPACITIES	AND AND ASSESSMENT OF THE SAME
Fuel Tank	50 Ltr
Engine Oil Sump	6.9 Ltr
Transmission /Hydraulic Oil	35.9 Ltr
Steering Box	0.9 Ltr
Oil Bath, Air Cleaner	0.5 Ltr
Cooling System	10.5 Ltr
OVERALL DIMENSIONS	
Length	3200 mm
Width	1880 mm
Height	2225 mm
Ground Clearance	520 mm
WEIGHT	
Gross Weight (Kgs)	1970 Kg



0853-363892



0300-0657945



© 021 35205532 - Ext. 336



info@orienttractors.com customersupport@orienttractors.com